



s u m m a r y HYDRAULIC

Every day our filters and our filter elements efficiently satisfy the filtration requirements of countless applications all over the world.

Wherever a hydraulic or lubrication system is operating, on fixed or mobile applications, FILTREC filters The performances of our filter elements are validaand filter elements ensure the correct oil cleanliness to maintain the system's efficiency and reliability.

Our continuously evolving and expanding range of filter assemblies covers suction, pressure and return applications, to effectively solve the contamination control requirements of hydraulic systems.

ted by vigorous laboratory tests performed according to the most recent ISO specifications.

return series (tank top)



FRT SERIES up to 900 l/min 8 bar G 1/2" ÷ G 2" Extension tube Connection tube Diffuser Bypass 1,7 or 3 bar

FRM SERIES FR6 SERIES up to 300 l/min up to 400 l/min 10 bar 10 bar G 3/4" ÷ G 1 1/4" Extension tube Extension tube Connection tube Connection tube Diffuser Diffuser Dipstick Air breather Addittional ports Bypass 1,7 or 3 bar



FRP SERIES up to 300 l/min 10 bar G 1 1/2" G 1 1/4"+G 3/4"+G 1" Extension tube Connection tube Diffuser Dipstick Addittional ports Air breather Bypass 1,7 or 3 bar AEB valve 0,4 bar Bypass 3 bar



FCR7F-1 SERIES up to 400 l/min 10 bar G 1"-G1 1/4" G 1 1/2" Bypass 1,7 or 3 bar





FVR7F SERIES up to 3500 l/min 10 bar Bypass 1,7 or 3 bar

in line series



F040 SERIES up to 400 l/min F040 DMD000 5-8-11: 70 bar G 3/4" F040 DMD00 15-30-45: 40 bar G 1 1/4" No bypass or 3,5 bar



F100 SERIES up to 400 l/min F100-XD040/ 063/100: 100 bar G 1/2"÷ G 1" F100-XD160/



250 bar

G 1/2"



F050 SERIES

filter element

50 bar

G 1 1/4"

up to 400 l/min

Bypass inbuilt in the

S version 0,25 bar

3 version 3 bar

FH250 SERIES up to 50 l/min No bypass or 6 bar

FH320 SERIES up to 150 l/min 320 bar G 1/2"÷1"- M22x1,5 No bypass or 6 bar

FH420 SERIES THREADED up to 500 l/min up to 420 bar G 1/2" ÷ G 1 1/2" Bypass 6 bar ABF valve ABF valve+RF valve



FDM SERIES

315 bar

CETOP 03

CETOP 05

No bypass

up to 40 l/min





FML320 SERIES up to 500 l/min up to 320 bar Manifold block mounting Bypass 6 bar ABF valve

FDD040 040 400 SERIES up to 400 l/min up to 63 bar G 1" - G 1 1/2" Bypass 3,5 bar



250/400: 80 bar G 1 1/4"÷1 1/2" No bypass or 6 bar



FD3 SERIES up to 50 l/min 110 bar G 1/2" No bypass or 6 bar



FH100 SERIES up to 300 l/min 100 bar G 1" ÷ G 1 1/4" ABF or ABF+RF valve No bypass or 3,5 bar





FH420 SERIES FLANGED up to 500 l/min up to 420 bar 3/4" ÷1 1/2" SAE FLANGE METRIC SCREWS Bypass 6 bar ABF valve



KH420 SERIES up to 500 l/min 420 bar





FDD315 SERIES up to 400 l/min up to 315 bar G 1″ G 1 1/2" SAE Flange 1 1/2" Bypass 7 bar



FDD040 630 1000 SERIES up to 1000 l/min 40 bar SAE Flange 2 1/2" Bypass 3,5 bar

s u m m a r y HYDRAULIC

in line series









FLR SERIES (U5 - RHR - R4) up to 2600 l/min 30 bar 3"- 4" SAE 3000 FLANGE No bypass or up to 6 bar

FLRD SERIES **FLC SERIES** (U5 - RHR - R4) 350 bar up to 1600 l/min G 1/4" - G 3/8" 16 bar G 1/2" 3" SAE 3000 FLANGE DIN PN16 DN80 4" SAE 3000 FLANGE DIN PN16 DN100 No bypass or up to 6 bar



suction series



FS1 SERIES from G 3/8" ÷ G 4" Options: Bypass 0,25 bar

FS7 SERIES up to 200 l/min G 1" - G 1 1/4" G 1 1/2" SAE flange 1 1/2" 3000 psi No bypass or 0,3 bar



FS5 SERIES up to 100 l/min G 1 1/4″ No bypass or 0,3 bar

spin on series





FA1 SERIES 12 bar G 3/4" ÷ G 1 1/2" Suction: Bypass 0,25 bar In line / Return: No bypass or 1,7 bar





FAH SERIES up to 17 bar G 3/4"÷G 1 1/4" Bypass 3,5 bar FAHD SERIES up to 14 bar G 1 1/2"-G 1 1/4" + 1 1/2" SAE Flange Bypass 3,5 bar

FA2 SERIES 12 bar G 3/4" ÷ G 1 1/2" Bypass 1,7 bar

fluid management





FUH015 SERIES Hydraulic oil transfer and filtration portable unit 15 l/min

FUH050/100 SERIES Transfer and filtration portable unit FUH050: 50 l/min FUH100: 100 l/min

FUVD040 SERIES Oil vacuum dehydrator and filtration unit 40 l/min









FA4 SERIES up to 250 l/min up to 35 bar G 3/4" ÷ G 1 1/4" No bypass or 3,5 bar



FA5 SERIES up to 250 l/min 24 bar G 1 1/4" No bypass





FMSC SERIES Particles counter monitor 420 bar ISO 4406 SAE AS4059 NAS 1638 GOST 17216



FMSS SERIES Moisture and temperature sensor 50 bar 0÷100% r.H. -20 °C +120 °C

s u m m a r y HYDRAULIC

accessories



AIR FILTER AND FILLER BREATHERS Wide range of air filter and filler breathers offers the suitable solution to various requirements.

FL SERIES Visual, electric fluid level gauge With or without thermometer



INDICATORS Visual, electric pressure or differential indicator



FBD SERIES Dessicant breathers Air filtration 3μm absolute



FBM SERIES Pressurized air breather filters, with replaceable filter element notes



www.filtrec.com