

HYDRAULIC C



S II M M a r y HYDRAULIC

Every day our filters and our filter elements efficiently satisfy the filtration requirements of countless applications all over the world.

Wherever a hydraulic or lubrication system is operating, on fixed or mobile applications, FILTREC filters The performances of our filter elements are validaand filter elements ensure the correct oil cleanliness to maintain the system's efficiency and relia-

Our continuously evolving and expanding range of filter assemblies covers suction, pressure and return applications, to effectively solve the contamination control requirements of hydraulic systems.

ted by vigorous laboratory tests performed according to the most recent ISO specifications.

return series (tank top)



FRT SERIES

up to 900 l/min 8 bar G 1/2" ÷ G 2" Extension tube Connection tube Diffuser Bypass 1,7 or 3 bar



FR6 SERIES

up to 300 I/min 10 bar G 3/4" ÷ G 1 1/4" Extension tube Connection tube Diffuser Dipstick Air breather Addittional ports Bypass 1,7 or 3 bar



FRM SERIES

up to 400 l/min 10 bar G 1 1/4"+G 3/4"+G 1" Extension tube Connection tube Diffuser Addittional ports Bypass 1,7 or 3 bar



FRP SERIES

up to 300 l/min 10 bar G 1 1/2" Extension tube Connection tube Diffuser Dipstick Air breather AEB valve 0,4 bar Bypass 3 bar



KRT SERIES

up to 900 I/min 8 bar Extension tube Connection tube Diffuser Air breather Addittional ports Bypass 1,7 or 3 bar



FCR7F-1 SERIES

up to 400 I/min 10 bar G 1"-G1 1/4" G 1 1/2" Bypass 1,7 or 3 bar



FCR7F-2-3 SERIES

up to 1200 l/min 10 bar G 1" - G 1 1/2" 1 1/4" SAE FLANGE 2" SAE FLANGE 2 1/2" SAE FLANGE Bypass 1,7 or 3 bar



FVR7F SERIES

up to 3500 I/min Bypass 1,7 or 3 bar

in line series



F040 SERIES up to 400 l/min

F040 DMD000 5-8-11: 70 bar G 3/4" F040 DMD00 15-30-45: 40 bar G 1 1/4" No bypass or 3,5 bar



F035 SERIES

up to 400 l/min

30 bar G 1 1/4" Bypass inbuilt in the filter element S version 0.25 bar 3 version 3 bar



F100 SERIES

up to 400 l/min F100-XD040/ 063/100: 100 bar G 1/2" ÷ G 1" F100-XD160/ 250/400: 80 bar G 1 1/4"÷1 1/2" No bypass or 6 bar



FD3 SERIES

110 bar G 1/2"



No bypass or 6 bar



up to 50 l/min



FH100 SERIES up to 300 I/min

100 bar G 1" ÷ G 1 1/4" ABF or ABF+RF valve No bypass or 3,5 bar



FH250 SERIES

up to 50 I/min 250 bar G 1/2" No bypass or 6 bar

FDM SERIES

315 bar

CETOP 03

CETOP 05

No bypass

up to 40 l/min



FH320 SERIES

FML320 SERIES

up to 500 I/min

up to 320 bar

Manifold block

mounting

ABF valve

Bypass 6 bar

up to 150 l/min 320 bar G 1/2"÷1"- M22x1,5 No bypass or 6 bar



FH420 SERIES THREADED

up to 500 l/min up to 420 bar G 1/2" ÷ G 1 1/2" Bypass 6 bar ABF valve ABF valve+RF valve



FH420 SERIES FLANGED

up to 500 l/min up to 420 bar 3/4" ÷1 1/2" SAE FLANGE METRIC SCREWS Bypass 6 bar ABF valve



KH420 SERIES up to 500 I/min

420 bar



FDD040 040 400

SERIES up to 400 l/min up to 63 bar G 1" - G 1 1/2" Bypass 3,5 bar



FDD315 SERIES

up to 400 l/min up to 315 bar G 1" G 1 1/2" SAE Flange 1 1/2" Bypass 7 bar



FDD040 630 1000 **SERIES**

up to 1000 I/min 40 bar SAE Flange 2 1/2" Bypass 3,5 bar

HYDRAULIC SUMMARY | 3/8 HYDRAULIC SUMMARY | 2/8

S II M M a r y HYDRAULIC

in line series



FLR SERIES (U5 - RHR - R4) up to 2600 l/min 30 bar 3"- 4" SAE 3000 FLANGE No bypass or up to 6 bar



FLRD SERIES (U5 - RHR - R4) up to 1600 l/min 16 bar 3" SAE 3000 FLANGE DIN PN16 DN80 4" SAE 3000 FLANGE DIN PN16 DN100 No bypass or up to 6 bar



FLC SERIES 350 bar G 1/4" - G 3/8" G 1/2"



FHLC SERIES 420 bar G 1/2" - G 3/4" M22x1,5 - M26x1,5

suction series



FS1 SERIES from G 3/8" ÷ G 4" Options: Bypass 0,25 bar



FS7 SERIES

up to 200 l/min

G 1" - G 1 1/4"

G 1 1/2"

SAE flange 1 1/2"

3000 psi

No bypass or 0,3 bar




FS5 SERIES up to 100 l/min G 1 1/4" No bypass or 0,3 bar

spin on series









up to 17 bar G 3/4"÷G 1 1/4" Bypass 3,5 bar FAHD SERIES up to 14 bar G 1 1/2"-G 1 1/4" + 1 1/2" SAE Flange Bypass 3,5 bar



FA2 SERIES12 bar
G 3/4" ÷ G 1 1/2"
Bypass 1,7 bar



FA4 SERIES

up to 250 I/min

up to 35 bar

G 3/4" ÷ G 1 1/4"

No bypass or 3,5 bar



FA5 SERIES up to 250 l/min 24 bar G 1 1/4" No bypass

fluid management



FUH015 SERIES
Hydraulic oil transfer
and filtration portable
unit
15 l/min



FUH050/100 SERIES Transfer and filtration portable unit FUH050: 50 l/min FUH100: 100 l/min



FUVRO50 SERIES
A portable offline
filtration unit designed
to reduce or eliminate
varnish in hydraulic
and lubrication systems, without a chiller



PUF050 SERIES
Designed for superior performance, it offers dual filtration to remove water and solid contaminants, ensuring your diesel remains clean and efficient.



FUVD040 SERIES
Oil vacuum dehydrator
and filtration unit
40 l/min







FMSS SERIES
Moisture and
temperature sensor
50 bar
0÷100% r.H.
-20 °C +120 °C

HYDRAULIC SUMMARY | 4/8 HYDRAULIC SUMMARY | 5/8

accessories









AIR FILTER AND FILLER BREATHERS Wide range of six filter

Wide range of air filter and filler breathers offers the suitable solution to various requirements.

FL SERIES

Visual, electric fluid level gauge With or without thermometer

CLOGGING INDICATORS

Visual, electric pressure or differential indicator





absolute

Air filtration 3μm



FBM SERIES

Pressurized air breather filters, with replaceable filter element

notes



www.filtrec.com